

**DFE
DUAL DISCHARGE CEILING UNIT COOLERS**

All the DFE units may be used as either refrigerant evaporators or refrigerant condensers.

PS max allowable pressure : 28 bar abs.
 TS max allowable refrigerant temperature : 125 °C
 State of fluid contents : GAS
 Type of pressure equipment : PIPING

The reference table for the assessment of category is table n.6.

Models with external diameter connections up/equal to 25 mm are covered by art. 3 par. 3
 Models with external diameter connections from 25 mm up/equal to 35 mm are covered by Category I

Model	Category
DFE38-3, DFE28-7, DFE76-3, DFE57-7	Article 3 Paragraph 3
DFE115-3, DFE85-7, DFE153-3, DFE113-7, DFE191-3, DFE141-7, DFE229-3, DFE170-7	Category I
each model f/b option codes	

This units are for use with refrigerants dangerous (group 1) and non dangerous (group 2), following a list of most common refrigerants R22, R134a, R404A, R290, R600a, R12, R502, R507, R402A, R401A, R407A, R407C, R410A, R124.

Hazards arising from misuse :

- Consideration should be given to handling of units to point of assembly in order to avoid damage.
- The need for protection of hairpin and return bends should be considered in the final application
- Consideration must be given to galvanic corrosion Al-Cu on the end use application
- This units shall not be used with Ammonia R717