

EU Declaration of Conformity

Henry Technologies hereby declare under our sole responsibility that the Pressure Equipment listed below has been designed, manufactured and tested in accordance with the requirements of the Pressure Equipment Regulations (European Directive 2014/68/EU).

Description of Pressure Equipment: Safety Relief Valves

Model no.:

Pressure setting: Barg

Quantity:

Batch no.:

Conformity and Assessment Procedure followed: Product Category: Cat IV Modules: B + D Set Pressure range: 31.0 to 130.0 barg (5700, 5702, 5702A, 5702B, 5702C) 46.0 to 130.0 barg (5701AX)

Valve Parameters

Model Number	5700, 5701AX, 5702, 5702A, 5702B, 5702C		
Maximum Operating Temperature	+ 150°C		
Minimum Operating Temperature	- 40°C		

Standard Pressure Settings (barg)									
31.0*	40.0*	42.0*	45.0*	46.0	60.0	80.0	100.0	120.0	130.0
	*5701AX minimum setting = 46.0 barg								

Design Strength Test Pressure on all models = 195 barg (Type Approval)

Model no.	Orifice size	Type Certificate no.	Fluid Group
5700	3.5mm	CE-0041-PED-B3.1-HEN 001-17-GBR	2*
5701AX	7.1mm	CE-0041-PED-B-HEN-001-16-GBR	2*
5702/A/B/C	10.5mm	CE-0041-PED-B3.1-HEN 002-16-GBR	2*

*Also Suitable for Group 1 gas; Propane (R290).

The following transposed European standards and other technical specifications have been used: EN ISO4126-1: 2013 ASME VIII Division 1

The Notified Body which inspected the manufacturer's quality assurance system:

Bureau Veritas UK LTD. Parklands Wilmslow Road Didsbury Manchester M20 2RE

Notified Body identification No. 0041



Ronnie Crancher

QUALITY MANAGER Henry Technologies Ltd

DESIGNED FOR PERFORMANCE