

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name: Acryl-Lackspray A 6944**
- **Application of the substance / the preparation Color spray**
- **Manufacturer/Supplier:**
 Streicolor AG
 Lack- und Farbenfabrik
 Niederwil
 CH- 8502 Frauenfeld
 Tel.: +41 (0)52 723 215 0
 Fax: +41 (0)52 723 216 9
 email: info@streicolor.ch
- **Further information obtainable from: Laboratory**
- **Information in case of emergency: +49(0)5262-9939657 (MIP)**

2 Hazards identification

- **Hazard description:**



Xi Irritant
F+ Extremely flammable

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
Has a narcotizing effect.
R 12 Extremely flammable.
R 36 Irritating to eyes.
R 66 Repeated exposure may cause skin dryness or cracking.
R 67 Vapours may cause drowsiness and dizziness.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
Buildup of explosive mixtures possible without sufficient ventilation.
Keep out of the reach of children
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone Xi, F; R 11-36-66-67	25-50%
CAS: 106-97-8 EINECS: 203-448-7	butane F+; R 12	10-25%

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 1)

CAS: 74-98-6 EINECS: 200-827-9	propane F+; R 12	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi; R 10-36	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, Xi, N; R 10-37-51/53-65-66-67	≤ 2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.

(Contd. on page 3)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 2)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Do not seal receptacle gas tight.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44°C

· Flash point: < 0°C (DIN 53213)

· Ignition temperature: 365°C (DIN 51794)

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
Upper: 13.0 Vol %

· Vapour pressure at 20°C: 8300 hPa

· Density at 20°C: 0.707 g/cm³ (DIN 53217)

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Solvent separation test: < 3 %

· Solvent content:

Organic solvents: 86.5 %
VOC (EC) 611.6 g/l

· Solids content (weight-%): 13.5 %

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Dangerous decomposition products: Carbon monoxide

11 Toxicological information

- Acute toxicity:
- Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 4)

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

14 06 03	other solvents and solvent mixtures
15 01 04	metallic packaging
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 5)

· Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label: 2.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable

15 Regulatory information

· Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

- Xi Irritant*
- F+ Extremely flammable*

· Risk phrases:

- 12 Extremely flammable.*
- 36 Irritating to eyes.*
- 66 Repeated exposure may cause skin dryness or cracking.*
- 67 Vapours may cause drowsiness and dizziness.*

· Safety phrases:

- 2 Keep out of the reach of children.*
- 3 Keep in a cool place.*
- 9 Keep container in a well-ventilated place.*
- 23 Do not breathe fumes/aerosol.*
- 46 If swallowed, seek medical advice immediately and show this container or label.*
- 51 Use only in well-ventilated areas.*

· Special labelling of certain preparations:

- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.*
- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.*
- Buildup of explosive mixtures possible without sufficient ventilation.*
- Keep out of the reach of children*

· National regulations:

· Information about limitation of use:

112-07-2	2-butoxyethyl acetate	4
1344-28-1	aluminium oxide	2
14807-96-6	Talk	3B
14808-60-7	Quartz (SiO ₂)	1

Class	Share in %
NK	50-100

GB

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 20.04.2009

Revision: 20.04.2009

Trade name: Acryl-Lackspray A 6944

(Contd. of page 6)

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 *Flammable.*

11 *Highly flammable.*

12 *Extremely flammable.*

36 *Irritating to eyes.*

37 *Irritating to respiratory system.*

51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

65 *Harmful: may cause lung damage if swallowed.*

66 *Repeated exposure may cause skin dryness or cracking.*

67 *Vapours may cause drowsiness and dizziness.*

· * *Data compared to the previous version altered.*

GB