



## **REFCO New Products**



## Agenda

**REFMESH ENVIRO-DUO-EX ECO-A2L FLARE-e VAMP** 

Acknowledged globally



# Swiss premium manufacturer of tools and accessories for refrigeration technicians



## Benefits



## FULL PRODUCT RANGE




HIGH AVAILABILITY



#### SWISS QUALITY

More than 1.500 products for the professional HVAC/R technician.

> 98% of all products are available from our high rack warehouse in Switzerland. All our products live up to highest quality expectations.








## **Product range**



REFMESH Wireless Equipment



Charging hoses and valves



Test Equipment



Vacuum



Connectors



Installation Tools



Recovery and Charging



Leak Detection



Metallic Small Parts



Gauges



Condansate Handling



Automotive Equipment



Manifolds



Control and Measuring Devices




Rubber, Plastics and Chemicals

Acknowledged globally









## **REFMESH**

| REFMATE    |
|------------|
| REFVAC     |
| TRITECTOR  |
| REFCLAMP   |
| REFSCALE-S |

Acknowledged globally





# REFMATE

Digital manifold



REFMESH DIGITAL REPORTING



## REFMATE

The REFMATE is the Digital Manifold for the professional refrigeration engineer.



#### **FEATURES AND BENEFITS**

- Large 4.3" TFT display
- Indication of superheating and subcooling
- Intuitive control via robust push buttons
- High precision with accuracy class 0.5
- Flexible power supply (AA batteries or USB)
- Wireless communication with REFMESH App and other devices
- All mechanical components are available as spare parts
- Lockable for long-term measurements

Acknowledged globally





# REFVAC-RC

Digital vacuum gauge







## **REFVAC-RC**

The REFVAC-RC is the optimal device for checking the evacuation process on the construction site or in the laboratory.



- Integrated display
- High precision
- High resolution in low vacuum
- Wireless communication
- Signal range 100 m
- Intuitive handling
- Flexible power supply with USB





# TRITECTOR

3-in-1 Leak Detector







## **TRITECTOR**

The TRITECTOR™ is the practical 3-in-1 solution for the professional refrigeration engineer.



- Intuitive handling
- Intelligent electronics that automatically detect the connected sensor
- Exchangeable sensors for refrigerants, combustible gases and tracer gases
- Variable power supply (batteries & USB)
- Automatic and manual reset of the ambient concentration
- High quality LCD display






# REFCLAMP

Wireless temperature and humidity clamp





## **REFCLAMP**





- Sensors for temperature measurement on the pipe and the ambient air
- Integrated humidity sensor
- Wireless data transmission (> 300 m)
- Strong springs for secure installation on pipes with 6
   41 mm (1/4" 15/8") diameter
- Ergonomic design for easy handling
- Simple operation with two buttons






# REFSCALE-C

Electronic charging scale











## REFSCALE-C

Measures the exact quantities of refrigerant extracted and filled



- Compact and elegant design with handle
- Integrated display
- Weight 3.2 kg
- Weight capacity up to 100 kg
- Accuracy 0.05%
- High resolution of 2 g
- Programmable alarm
- Memory function



## REFSCALE-C

Measures the exact quantities of refrigerant extracted and filled



- Independent or connected wireless with REFMATE™ and/or REFMESH™
- Flexible power supply via battery or USB
- Sturdy green case for transport and protection
- Thread for attaching valve (optional accessory) for small refrigerant bottles







# REFVALVE

Switching valve for REFSCALE-C





### REFVALVE



Switching Valve for REFSCALE-S/-C

- Wireless connection of RESCALE-S, REFSCALE-C, and REFMATE with REFVALVE
- Automatic filling to target value of refrigerant weight, superheat, or subcooling
- Fail-safe operation: automatic closing when system is turned on and off
- Target Superheat automatic filling for optimizing superheat
- Suitable for all refrigerants up to 40 bar versatile
- Hook for flexible hanging



ENVIRO-DUO-

EX

ATEX certified recovery station







## **ENVIRO-DUO-EX**



ATEX-certified recovery station
II 3G EX EC ic NC h IIA T4 Gc

- Suitable for refrigerants of class A1, A2, A2L (R32, R1234 yf/R 1234 ze) and A3 (R290, R600a)
- Digital display
- Easy to use
- High-speed recovery, up to 501 kg/h (Push-pull mode, R 410 A)
- Weight 12.8 kg





# ECO-A2L

Vacuum pumps for A2L refrigerants





## ECO-3/5/9-A2L



High-performance vacuum pumps for A2L refrigerants

- Three available versions 84/142/255 I/min
- Two stage
- Compact design and dimensions, low weight
- Low noise level
- End vacuum 15 microns
- 1/4" and 3/8" SAE connections
- Integrated solenoid valve



# ECO-2-A2L-e

Battery vacuum pump for A2L refrigerants





## ECO-2-A2L-e

Battery vacuum pump for A2L refrigerants



- Two stage
- Flow rate 57 I/min.
- Compact design and dimensions
- Weight 3.2 kg (without battery)
- End vacuum 15 microni
- 1/4" SAE connection
- Integrated solenoid valve
- 50 minutes operation with fully charged battery





# FLARE-e

Battery-driven flaring tool







## **FLARE-e**

Battery-driven flaring tool



- No room for mistakes: perfect and rapid 45° flares
- Lightweight (1.1 kg) and compact
- 135 flares with 100% charged battery
- 6 heads in mm (6-18 mm) or inches (1/4-3/4")
- Maximum work safety: 2 safety features





VAMP-F

Condensate pump with integrated reservoir and optical level sensor





## **VAMP-F**



Condensate pump with integrated reservoir and optical sensor, for units up to 63 000 BtU

- Suitable for every challenge: 26 mm height
- Easy to install: no external sensor
- Internal optical sensor with multiple detection levels
- Extendable posable hose for quick installation
- Extremely quiet < 20 dBA</li>
- Flow of 22 I/h, head of 15 m
- Adapters available for easy installation
- Made in Switzerland





# VAMP-X

Condensate pump with external sensor





## VAMP-x



Condensate pump with external sensor, for units up to 63 000 BtU

- Suitable for every challenge: 26 mm height
- External optical sensor with multiple detection levels
- Extendable posable hose for quick installation
- Extremely quiet < 20 dBA
- Flow of 22 l/h, head of 5 m, suction of 2 m
- Adapters available for easy installation
- Made in Switzerland



# There are countless reasons to become a Fan of REFCO.



