

	iMINILide1	iMINILide2	iMINILide3	iMINILide4	iMINILide8	iMINILide16	iMINILide32
INPUTS							
Range of temperature recordable From -100°C to +300°C	✓	✓	✓	✓	✓	✓	✓
Input(s) for probe(s) PT100	✓	✓	✓	✓	✓	✓	✓
Probe(s) inside the pack PT100 (-30°C + 80°C)	One	Two	Three	Four	Six	Ten	Zero
Input(s) for free contact(s)	✓	✓	✓	✓	✓	✓	✓
Accept 4-20 mA sensors (humidity, CO2, pressure, etc...) Kit 4-20 mA in option	○	○	○	○	○	○	○
OUTPUTS (alarm)							
1 Alarm relay / contact	✓	✓	✓	✓	✓	✓	✓
Kit 2 relays for alarm in option	-	-	-	○	○	○	○
MEMORY							
Capacity for the datas	One year	One year	One year	One year	One year	One year	One year
BATTERY (included inside the iMINILide)							
Capacity	3 hours	3 hours	3 hours	From 12 to 8 hours			
FULL WEB PACK							
Web access included (LIFETIME)	✓	✓	✓	✓	✓	✓	✓
Alarm alert by Email	✓	✓	✓	✓	✓	✓	✓
Check graphics from your smartphone or PC	✓	✓	✓	✓	✓	✓	✓
Check alarms from your smartphone or PC	✓	✓	✓	✓	✓	✓	✓

Option not possible	-
Option available	○
Included inside the pack	✓